

# 補 償 導 線

E X : 紫色

R X : 黑色外被

K X : 藍色外被

W X : 藍色外被

V X : 藍色外被(K TYPE)

※PVC外被可指定銅網內隔離

J X : 黃色外被

※玻璃纖維外被可指定鍍錫銅網外隔離

T X : 茶色外被

VVF : PVC外被

GGF : 玻璃絲外被

※另可訂製多對數型

產品類別	規 格	導 體 構 造	絕緣厚度mm	絕緣外徑mm	被覆厚度mm	完成外徑mm
VX-H=GGF	7/0.30×1P	7C/0.30MM	0.4	1.7	0.3	2.3×4.0
VX-H=GGF	4/0.65×1P	4C/0.65MM	0.4	2.37	0.3	3.0×5.4
VX-H=GGF	7/0.65×1P	7C/0.65MM	0.4	2.75	0.3	3.4×6.2
VX-H=VVF	7/0.30×1P	7C/0.30MM	0.5	1.9	0.6	3.1×5.0
VX-H=VVF	4/0.65×1P	4C/0.65MM	0.6	2.77	0.8	4.4×7.2
VX-H=VVF	7/0.65×1P	7C/0.65MM	0.6	3.15	0.8	4.8×7.9
JX-H=GGF	7/0.30×1P	7C/0.30MM	0.4	1.7	0.3	2.3×4.0
JX-H=GGF	4/0.65×1P	4C/0.65MM	0.4	2.37	0.3	3.0×5.4
JX-H=GGF	7/0.65×1P	7C/0.65MM	0.4	2.75	0.3	3.4×6.2
JX-H=VVF	7/0.30×1P	7C/0.30MM	0.5	1.9	0.6	3.1×5.0
JX-H=VVF	4/0.65×1P	4C/0.65MM	0.6	2.77	0.8	4.4×7.2
JX-H=VVF	7/0.65×1P	7C/0.65MM	0.6	3.15	0.8	4.8×7.9
TX-H=GGF	7/0.30×1P	7C/0.30MM	0.4	1.7	0.3	2.3×4.0
TX-H=GGF	4/0.65×1P	4C/0.65MM	0.4	2.37	0.3	3.0×5.4
TX-H=GGF	7/0.65×1P	7C/0.65MM	0.4	2.75	0.3	3.4×6.2