



Feed-Through	HT-2.5		HT-4		HT-10		HT-16		HT-35		HT-50		HT-95	
Terminals														
Screw clamp connection														
Material : PA66														
Rail mount on TS32/TS35 or direct mounting														
Qty. p. pck (g/pcs)	1320/200		1100/100		1630/100		1480/50		1156/20		5835/50		4695/25	
Terminal width/Insulation stripping length	5.1mm/7mm		6.2mm/11.5mm		8.4mm/12mm		12.3mm/15mm		16.2mm/18mm		20.3mm/27mm		25.5mm/30mm	
Conductor cross-section solid/stranded	0.2-4/0.2-2.5		0.2-6/0.2-4		0.2-10/0.2-10		2.5-25/2.5-16		2.5-50/2.5-35		16-50/25-50		35-95/35-95	
AWG	22-12		22-10		22-8		12-6		12-2		6-1/10		2	
Electrical ratings	Voltage V	Current A	Voltage V	Current A	Voltage V	Current A	Voltage V	Current A	Voltage V	Current A	Voltage V	Current A	Voltage V	Current A
VDE	750	26	750	34	750	55	750	75	750	135	1000	168	1000	250
CE	600	24	600	30	600	50	600	70	600	100	600	150	600	230
UL	600	20	600	30	600	50	600	70	600	115	600	150	600	115
End Plate	EP-4		EP-4		EP-4		EP-16		EP-35		-		-	
Color	Grey		Grey		Grey		Grey		Grey		Grey		Grey	
Approvals	