



FEATURES

- Accuracy: $\pm 0.1\%$ R.O.
- Wide input and output range selection
- Steady voltage, current and low ripple output
- Plug-in type




MODEL: S4 - DT - [] - [] - [] - F

NO.	DC Input Range	NO.	DC Output Range	Load R.	NO.	Power Supply
V1	0 ~ 10mV	10	0 ~ 100mV	$\geq 100K\Omega$	1	AC 110V
V2	0 ~ 100mV	11	0 ~ 1V	$\geq 500\Omega$	2	AC 220V
V3	0 ~ 1V	12	0 ~ 5V	$\geq 500\Omega$	3	DC 110V
V4	0 ~ 5V	13	0 ~ 10V	$\geq 500\Omega$	4	DC 48V
V5	1 ~ 5V	14	1 ~ 5V	$\geq 500\Omega$	5	DC 24V
V6	0 ~ 10V	15	-10 ~ 10V	$\geq 5K\Omega$	0	Option
V7	-10 ~ 10V	16	0 ~ 1mA	$\geq 10K\Omega$		
V8	0 ~ 100V	17	0 ~ 10mA	$\geq 1.5K\Omega$		
A1	0 ~ 1mA	18	0 ~ 20mA	$\geq 750\Omega$		
A2	0 ~ 10mA	19	4 ~ 20mA	$\geq 750\Omega$		
A3	0 ~ 20mA	20	20 ~ 4mA	$\geq 750\Omega$		
A4	4 ~ 20mA	00	Option			
00	Option					

SPECIFICATION

Accuracy..... $\pm 0.1\%$ R.O.
Power supply..... AC 110 V $\pm 15\%$, 50/60HZ
AC 220 V $\pm 15\%$, 50/60HZ
DC 24V,48V,110V $\pm 10\%$
Power consumption..... AC $\leq 5VA$,DC $\leq 3W$
Input resistance..... $\geq 100K\Omega$ (mV)
 $\geq 1M\Omega$ (V)
 $\geq 50\Omega$ (20mA)
Response time..... $\leq 500 \mu sec$
Output ripple..... $\leq 0.5\%$ R.O.(peak-peak)
Span adjustment range..... $\geq \pm 20\%$ R.O.
Zero adjustment range..... $\geq \pm 10\%$ R.O.
Operating temperature rang..... 0 ~ 60°C
Storage temperature rang..... -10 ~ 70°C
temperature rang coefficient..... $\leq 150PPM/^\circ C$
Max. relative humidity..... 95%
Isolation..... Input/Output/Power/Case
Insulation resistance..... $\geq 100M\Omega$, DC 500 V
Dielectric strength..... Input/Output/Power AC1.8KV/minute
All terminal/Case AC1.8KV/minute
Impulse withstand test..... 3KV, 1.2 x 50 μs
Common mode & Differential mode

DIMENSIONS (UNIT : mm)



CONNECTION DIAGRAM

