


Connectors




Shark Connector IP44

Poles	16 Amp			32 Amp		
	3	4	5	3	4	5
a	133	138	145	161	161	168
b	74	82	89	94	94	99
K_cable Ø [mm]	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22
Connection type:	Screw terminal					
Wire flexible [mm ²]	1-2,5			2,5-6		
Contact screws [Ncm]	100 Ncm			110 Ncm		
SW	42	42	42	50	50	50
Weight [g]	134	161	188	228	244	270

- with screw terminals
- housing material: PA6
- contacts: brass
- to order nickel-plated contacts please add a "v" e.g. 215-6v

IP44 splashproof




Turbo Shark Connector IP44

Poles	16 Amp			32 Amp		
	3	4	5	3	4	5
a	133	138	145	161	161	168
b	74	82	89	94	94	99
K_cable Ø [mm]	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22
Connection type:	Screwless terminal					
Wire flexible [mm ²]	1-2,5			2,5-6		
SW	42	42	42	50	50	50
Weight [g]	136	161	193	228	243	271

- screwless connection technology
- housing material: PA6
- contacts: brass
- to order nickel-plated contacts please add a "v" e.g. 215-6TTv

IP44 splashproof




Shark Connector IP66/67

Poles	16 Amp			32 Amp		
	3	4	5	3	4	5
a	132	139	147	163	163	171
b	78	84	92	96	96	102
K_cable Ø [mm]	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22
Connection type:	Screw terminal					
Wire flexible [mm ²]	1-2,5			2,5-6		
Contact screws [Ncm]	100 Ncm			110 Ncm		
SW	42	42	42	50	50	50
Weight [g]	155	186	227	275	292	338

- with screw terminals
- housing material: PA6
- contacts: brass
- to order nickel-plated contacts please add a "v" e.g. 2152-6v

IP66/67 watertight



Turbo Shark Connector IP66/67

Poles	16 Amp			32 Amp		
	3	4	5	3	4	5
a	132	139	147	163	163	171
b	78	84	92	96	96	102
K_cable Ø [mm]	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22
Connection type:	Screwless terminal					
Wire flexible [mm ²]	1-2,5			2,5-6		
SW	42	42	42	50	50	50
Weight [g]	157	187	231	275	291	339

- screwless connection technology
- housing material: PA6
- contacts: brass
- to order nickel-plated contacts please add a "v" e.g. 2152-6TTv

IP66/67 watertight

