

漏電斷路器 漏電、過負載、短路保護兼用型



框架容量 (AF)	50								50								50			
型 式	KSB-150	KSB-250				KSB-350				KCB-150	KCB-250				KCB-350				KHB	
極 數 (P)	—	E	F	G	H	E	F	G	H	—	E	F	G	H	E	F	G	H	150S 250S	
額定電流 I_n (A) (AT) 基準周圍溫度 40°C	1	2				3				1	2				3				1 2	
相 線 式	1 ϕ 2W	1 ϕ 2W				1 ϕ 2W 1 ϕ 3W 3 ϕ 3W				1 ϕ 2W	1 ϕ 2W				1 ϕ 2W 1 ϕ 3W 3 ϕ 3W				1 ϕ 2W	
額定靈敏度電流 (mA)	30	30	100	200	300	30	100	200	300	30	30	100	200	300	30	100	200	300	30 100 300 500	
動作時間 (秒)	0.1秒以下	0.1秒以下				0.1秒以下				0.1秒以下	0.1秒以下				0.1秒以下				0.1秒以下	
外型及安裝尺寸 	a	25.5	51				75.5				25.5	51				75.5				25 50
	b	110.5	97				97				110.5	97				97				105
	c	61	60.5				60.5				61	60.5				60.5				60
	ca	77	76.5				76.5				77	76.5				76.5				77 80
	bb	120.7	105.2				105.2				120.7	105.2				105.2				118.8
	aa	—	25.2				50.2				—	25.2				50.2				— 25
	(mm)																			
製品重量 (kg)	0.22	0.35				0.49				0.22	0.35				0.49				0.23 0.37	
額定電壓V (AC)	110/220V	110/220V				220/380V				110/220V	110/220V				220/380V				110/220V	
CNS 5422 額定斷路容量 (kA) AC Icu	110V	5	5				—				10	10				—				15 —
	220V	5	5				5				10	10				10				10 15
	380V	—	—																	