


0607 KSS 電纜固定頭轉接頭 REDUCTION GLAND



材質：UL合格之NYLON66，防火等級 94V-2。
用途：此產品可將固定頭的螺紋外徑由小尺寸轉換成大尺寸。



※標準色為黑色

單位：mm

型號 Item No.	外螺紋規格 D1				內螺紋規格 D2		寬度 W	包裝 Packing
	螺紋規格 Thread	螺紋外徑 Thread O.D.	鐵板孔徑 Mounting Hole	螺紋長度 L1	螺紋規格 Thread	螺紋長度 L2		
M2012	M20X1.5	20	20+0.2	8.0	M12X1.5	11.0	24.2	100pcs
M2016	M20X1.5	20	20+0.2	8.0	M16X1.5	12.0	24.2	
M2516	M25X1.5	25	25+0.3	8.0	M16X1.5	13.0	29.0	
M2520	M25X1.5	25	25+0.3	8.0	M20X1.5	14.0	29.0	
M3220	M32X1.5	32	32+0.3	10.0	M20X1.5	14.5	35.9	50pcs
M3225	M32X1.5	32	32+0.3	10.0	M25X1.5	15.0	35.9	
M4032	M40X1.5	40	40+0.3	10.0	M32X1.5	15.0	45.8	25pcs
M5040	M50X1.5	50	50+0.3	11.5	M40X1.5	15.0	55.0	
M6350	M63X1.5	63	63+0.3	11.5	M50X1.5	11.5	67.5	

※標準色為灰色

單位：mm

型號 Item No.	外螺紋規格 D1				內螺紋規格 D2		寬度 W	包裝 Packing
	螺紋規格 Thread	螺紋外徑 Thread O.D.	鐵板孔徑 Mounting Hole	螺紋長度 L1	螺紋規格 Thread	螺紋長度 L2		
M1612GY4	M16X1.5	16	16+0.2	8.0	M12X1.5	12.0	22.0	100pcs
M2512GY4	M25X1.5	25	25+0.3	8.0	M12X1.5	13.0	28.5	
M3212GY4	M32X1.5	32	32+0.3	10.0	M12X1.5	10.0	35.5	50pcs
M3216GY4	M32X1.5	32	32+0.3	10.0	M16X1.5	14.3	35.5	
M4016GY4	M40X1.5	40	40+0.3	10.0	M16X1.5	10.0	45.5	25pcs
M4020GY4	M40X1.5	40	40+0.3	10.0	M20X1.5	10.0	45.5	
M4025GY4	M40X1.5	40	40+0.3	10.0	M25X1.5	10.0	45.5	
M5020GY4	M50X1.5	50	50+0.3	12.0	M20X1.5	12.0	54.5	
M5025GY4	M50X1.5	50	50+0.3	12.0	M25X1.5	12.0	54.5	
M5032GY4	M50X1.5	50	50+0.3	12.0	M32X1.5	12.0	54.5	
M6325GY4	M63X1.5	63	63+0.3	12.0	M25X1.5	12.0	67.5	
M6332GY4	M63X1.5	63	63+0.3	12.0	M32X1.5	12.0	67.5	
M6340GY4	M63X1.5	63	63+0.3	12.0	M40X1.5	12.0	67.5	

配線槽

配線標誌

紮線帶

結束帶

固定座

固定頭、浪管

保護部品

接線頭

套管

固定夾

PC板部品

扣具