

■ 端子隔離蓋 TC

型名	適用 斷路器極數	適用斷路器機種		外型尺寸(mm)			
		MCCB	ELCB	長(A)	寬(B)	高(C)	外長(D)
TC100N 2P	2	NF30-SN. NF50-CN,SN,HN. NF100-CN,MN,SN.	—	50	51	55	34
TC100N 3P	3		NV30-SN. NV50-SN,HN.	75	51	55	34
TC100N 4P	4		100	56	55	30	
TC125N 2P	2	NF100-HN. NF125-SN,HN.	—	60	55	55	34
TC125N 3P	3	NF100-HN. NF125-SN,HN.	NV100-CN,MN,SN. NV125-SN,HN.	90	55	55	34
TC125N 4P	4			120	60	55	30
TC125T 3P	2	NF125-HT.	—	90	53	61	31
	3						
TC125T 4P	4	NF125-HT.	—	120	53	61	31
TC250N 3P	2	NF225-CN,SN./ NF250-CN,SN.	—	105	65	60.5	44
	3						
TC250N 4P	4	NF225-CN,SN. NF250-CN,SN,HT.	NV225-CN,SN. NV250-CN,SN,RT.	140	69	60.5	44
TC400N 3P	2	NF400-CN,SN,HN,UN.	—	171	148	95	110
	3						
TC400N 4P	4	NF400-CN,SN,HN,RN,UN,UE. NF630-ST,LT,HT.	NV400-CN,SN,HN,UN. NV630-HT.	240	148	95	110
TC630N 3P	3	NF800-CN,SN,HN,RN,SE,RE.	NV800-RN.	220	154.5	95	123
TC630N 4P	4			290	154.5	95	123
TC225 3P	3	NF250-HS.	—	105	67	77	40

■ 短端子隔離蓋 TC S

型名	適用 斷路器極數	適用斷路器機種		外型尺寸(mm)			
		MCCB	ELCB	長(A)	寬(B)	高(C)	外長(D)
TC100NS 2P	2	NF30-SN. NF50-CN,SN,HN. NF100-CN,MN,SN.	—	50	25	55	8
TC100NS 3P	3		NV30-SN. NV50-SN,HN.	75	25	55	8
TC100NS 4P	4		100	31	55	5	
TC125NS 2P	2	NF100-HN. NF125-SN,HN.	—	60	31	55	10
TC125NS 3P	3	NF100-HN. NF125-SN,HN,HT.	NV100-CN,MN,SN. NV125-SN,HN.	90	31	55	10
TC125NS 4P	4			120	35	55	5
TC125TS 3P	2	NF125-HT.	—	90	28	61	6
	3						
TC125TS 4P	4	NF125-HT.	—	120	28	61	6